(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 21 April 2005 (21.04.2005)

(10) International Publication Number WO 2005/035328 A2

(51) International Patent Classification7:

B60T

(21) International Application Number:

PCT/IB2004/003329

(22) International Filing Date: 12 October 2004 (12.10.2004)

(25) Filing Language:

(26) Publication Language:

English

(30) Priority Data:

10/684,877 60/513,085 13 October 2003 (13.10.2003) US

21 October 2003 (21.10.2003)

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:

US

10/684,877 (CIP)

Filed on

13 October 2003 (13.10.2003)

(71) Applicant: BERI, Michael [CA/CA]; 31 Codsell Avenue, North York, Ontario M3H 3V7 (CA).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FL GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US (patent), UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


of inventorship (Rule 4.17(iv)) for US only

Published:

without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: BRAKE SHOE AND BRAKE LINING BLOCKS WITH KEYED CONNECTION



plates are connected by a key or tang in one to a key way or slot in the content. I reassemble a more and the slot. Fasteners may be provided in the facilitate alignment of the brake plates with the brake shoe so that the key is received in the slot. Fasteners may be provided in the slot. Fasteners may be provided in the slot and the brake plate. four open corner areas so that the brake plate may be secured to the brake shoe with metal-to-metal contact where the brake plate is secured to the brake shoe. A brake shoe having a cylindrical outer surface or an outer surface defined by a plurality of flats is provided.